



3 Way Hard Line Outdoor Unbalanced Splitter

- 5-1000 MHz
- High Isolation, Low Thru-loss
- Captive Hardware to Prevent Loss During Installation
- Interlocking Tongue/Groove Plate
- Superior Interwoven Gasket, -100dB RFI Shielding
- Stainless Steel Clamp, can be used for Aerial or Pedestal Mounting
- Fused Output Ports
- Brass F-Port with Neoprene Gasket Seals
- Power Passing
- 360° Aluminum Drip Wells

TECHNICAL SPECIFICATIONS			
INSERTION LOSS (IN – OUT1 / OUT2,3) (dB)	5 – 65MHz	≤ 3.7dB	≤ 7.5 dB
	65 – 550MHz	≤ 3.8 dB	≤ 7.5 dB
	550 – 750MHz	≤ 4.2 dB	≤ 8.0 dB
	750 – 1000MHz	≤ 5.5 dB	≤ 8.0 dB
ISOLATION (OUT – OUT) (dB)	5 – 65MHz	≥ 25.0 dB	
	65 – 550MHz	≥ 24.0 dB	
	550 – 750MHz	≥ 24.0 dB	
	750 – 1000MHz	≥ 22.0 dB	
RETURN LOSS IN / OUT (dB)	5 – 65MHz	≥ 16.0 dB	
	65 – 550MHz	≥ 16.0 dB	
	550 – 750MHz	≥ 16.0 dB	
	750 – 1000MHz	≥ 16.0 dB	
Frequency range		5- 1000MHz	
Power Capability		15Amp @ 90Vac	
Hum Modulation		>70 dB (at 10 Amp)	
Impedance		75 ohm	
Connector		5/8” x 24 UNEF	