



4-WAY HARD LINE OUTDOOR TAPS

- 5-1000MHz
- High Isolation, Low Thru-loss
- Captive Hardware to Prevent Loss During Installation
- Interlocking Tongue/Groove Plate
- Superior Interwoven Gasket, -100dB RFI Shielding
- Stainless Steel Clamp, can be used for Aerial or Pedestal Mounting
- Fused Output Ports
- Brass F-Port with Neoprene Gasket Seals
- Power Passing
- 360° Aluminum Drip Wells

TECHNICAL SPECIFICATIONS

Item / dB Value		8	11	14	17	20	23	26
Insertion Loss (In - Out) dB	5 - 65 MHz	-	≤3.3	≤3.3	≤1.5	≤1.0	≤0.8	≤0.8
	65 - 550MHz	-	≤4.1	≤4.1	≤1.7	≤0.8	≤0.7	≤0.7
	550 - 750 MHz	-	≤4.6	≤4.6	≤2.3	≤1.2	≤0.8	≤0.8
	750 - 1000MHz	-	≤5.0	≤5.0	≤3.5	≤2.5	≤2.0	≤2.0
Tap Loss	5 - 1000MHz	±1.5	±1.8	±1.5	±1.5	±1.5	±1.5	±1.5
Isolation (Out - Tap) dB	5 - 65 MHz	-	≤22.0	≤26.0	≤30.2	≤28.0	≤30.0	≤30.0
	65 - 550MHz	-	≤28.0	≤28.0	≤28.0	≤28.0	≤29.0	≤29.0
	550 - 750 MHz	-	≤27.0	≤27.0	≤26.0	≤27.0	≤29.0	≤29.0
	750 - 1000MHz	-	≤22.0	≤22.0	≤24.0	≤26.0	≤26.0	≤26.0
Isolation (Tap - Tap) dB	5 - 1000MHz	≥ 22.0	≤22.0	≤22.0	≤22.0	≤22.0	≤22.0	≤22.0
In / Out / Tap Return Loss (dB)	5 - 1000MHz	≥ 16.0	≤16.0	≤16.0	≤16.0	≤16.0	≤16.0	≤16.0

Frequency range	5- 1000MHz
Power Capability	12 Amp
Hum Modulation	>65 dB (at 10 Amp)
Impedance	75 ohm
Connector	5/8" x 24 UNEF