

PV1S60V2RM

CABO COAXIAL RG11 60%MALHA PTO C/MENSAG BOB 305M

PERFECTVISION[®]



COD-Z: 44.30.119

PV1S60V2RM

CABO COAXIAL RG11 60%MALHA PTO C/MENSAG BOB 305M

PERFECTVISION[®]



COD-Z: 44.30.119

PV1S60V2RM

CABO COAXIAL RG11 60%MALHA PTO C/MENSAG BOB 305M

PERFECT*VISION*®



COD-Z: 44.30.119

PV1S60V2RM

CABO COAXIAL RG11 60%MALHA PTO C/MENSAG BOB 305M



SERIES 11, DUAL SHIELD, 60%, PVC, 0.072" MESSENGER

Outdoor Use

CONSTRUCTION CHARACTERISTICS

Conductor	Material:	Copper-Clad Steel
	Nominal OD:	0.064" \pm 1% (1.63mm \pm 1%)
Dielectric	Material:	OIT Stable, Foamed PE
	Nominal OD:	0.280" (7.11 mm)
Foil Shield	Material:	AL/PET/AL/EAA
	Shield Core OD:	0.288 \pm 0.006 inches (7.32 \pm 0.15 mm)
	Foil Shield Coverage:	100% (18% min. - 35% max. Overlap)
Braid Shield	Material:	34 AWG Aluminum Alloy
	Braid Coverage	60%
Corrosion Treatment	Material:	SafeGuard NT
Jacket(s)	Nominal OD	.400 \pm 0.010 inches (10.16 \pm 0.25 mm)
	Material	UV Stable PVC (-20°C Cold Impact)
	Color	Black
Messenger	Material:	0.072 \pm 0.002" (1.83 \pm 0.05mm)
	Minimum Break Strength	Galvanized Steel 346 lbf (156.9 kgf)



MAXPIPE

COD-Z: 44.30.119