



## 2 Way Hard Line Outdoor Splitter

- 5-1000 MHz
- High Isolation, Low Thru-loss
- Captive Hardware to Prevent Loss During Installation
- Interlocking Tongue/Groove Plate
- Superior Interwoven Gasket, -100dB RFI Shielding
- Stainless Steel Clamp, can be used for Aerial or Pedestal Mounting
- Fused Output Ports
- Brass F-Port with Neoprene Gasket Seals
- Power Passing
- 360° Aluminum Drip Wells

TECHNICAL SPECIFICATIONS		
INSERTION LOSS (IN – OUT) (dB)	5 – 65MHz	≤ 3.6 dB
	65 – 550MHz	≤ 3.8 dB
	550 – 750MHz	≤ 4.3 dB
	750 – 1000MHz	≤ 5.5 dB
ISOLATION (OUT – OUT) (dB)	5 – 65MHz	≥ 26.0 dB
	65 – 550MHz	≥ 28.0 dB
	550 – 750MHz	≥ 27.0 dB
	750 – 1000MHz	≥ 24.0 dB
RETURN LOSS IN / OUT (dB)	5 – 65MHz	≥ 16.0 dB
	65 – 550MHz	≥ 16.0 dB
	550 – 750MHz	≥ 16.0 dB
	750 – 1000MHz	≥ 16.0 dB
Frequency range		5- 1000MHz
Power Capability		15Amp @ 90Vac
Hum Modulation		>70 dB ( at 10 Amp )
Impedance		75 ohm
Connector		5/8" x 24 UNEF